

## TECHNICAL DATA SHEET – HPC 02 NU-GUARD TACK PRIMER

### DESCRIPTION:

Nu-Guard Tack Primer is a high performance water soluble, epoxy coating.

### ADVANTAGES:

Provides first class adhesion to properly prepared surfaces.

### USES:

First coat of the Nu-Guard AG System. Developed to act as a tack primer over existing coatings and non porous substrates including glazed tiles.

### COLOUR RANGE:

Off White.

### PACK SIZE:

Two component product, supplied in 5 litre units.

### VOLUME SOLIDS:

40%

### COVERAGE RATE:

8 m<sup>2</sup> / Litre

### DRYING TIME:

Touch :.....3 - 4 hours.

Overcoat : .....8 hours.

### PREPARATION:

Ensure surfaces to be treated are clean, free from contamination and dry. Previously coated surfaces should be abraded.

### APPLICATION:

By brush/roller or spray. Should not be applied at temperatures below 5°C or when the relative humidity exceeds 85%.

### EQUIPMENT CARE:

All equipment should be cleaned with water immediately after use.

### STORAGE:

Store away from direct sunlight and sources of heat. Protect from frost.

### SHELF LIFE:

12 months (in original sealed container).

### HEALTH & SAFETY:

Refer to MSDS