

ISSUE: 04/01/2024

TECHNICAL DATA SHEET

HPC 04 NU-GUARD AG ADHESION PROMOTER

DESCRIPTION:

Nu-Guard AG Adhesion Promoter is a modified Vinyl Acetate, non-flammable and non-toxic sealer. It is formulated primarily for use on glazed tiles.

ADVANTAGES:

Single pack ready for immediate use. Provides excellent adhesion to glazed tiles prior to the application of Nu-Guard AG Clear Finish.

USES:

To provide adhesion to tiles and other dense surfaces.

COLOUR RANGE:

Clear.

PACK SIZE:

Single component product, supplied in 5 and 25 litre drums.

COVERAGE RATE:

This is dependant upon the surface porosity. Average coverage rate is in the region of $8 - 12 \text{ m}^2$ per litre.

DRYING TIME:

Touch dry......10 - 30 minutes @ 20°C. Hard dry.....60 - 120 minutes.

PREPARATION:

Ensure surfaces to be treated are clean, free from contamination and dry. The surfaces should be washed off to provide a clean neutral surface and allowed to dry.

APPLICATION:

One coat by brush, roller or spray.

EQUIPMENT CARE:

All equipment should be cleaned with water

STORAGE:

Store away from direct sunlight and sources of heat. Protect from frost.

SHELF LIFE:

12 months (in original sealed container).

HEALTH & SAFETY:

Refer to MSDS.

Unit 7 Phoenix Road Wednesfield Wolverhampton WV11 3PX, UK

TEL: +44(0) 1902 450 950





