

TECHNICAL DATA SHEET – HPC 100 NU-FLAME TIMBERCOAT

DESCRIPTION:

Nu-Flame Timbercoat is an intumescent paint system for new and previously painted timber surfaces.

ADVANTAGES:

Being a water soluble product this is safe for internal applications. **Tested to BS 476 part 6 & 7 and satisfies Class '0' Requirements of current Building Regulations.**

USES:

For use on wood and timber.

COLOUR RANGE:

White / Pastel Colours

PACK SIZE:

Single component product, supplied in 20 Kg units.

COVERAGE RATE:

7 m² per Kg. 2 coats required

VOLUME SOLIDS:

60%

DRYING TIME:

Touch: 4 Hours
Overcoat: 16 Hours

PREPARATION:

If applying to existing painted timber, rub down thoroughly. Ensure surfaces are sound to provide a key, wash down and allow to dry. Do not apply in damp, cold conditions or when condensation may form on walls and ceilings.

APPLICATION:

By brush/roller or Airless Spray

EQUIPMENT CARE:

All equipment should be cleaned with water immediately after use

STORAGE:

Store away from direct sunlight and sources of heat. Protect from frost.

SHELF LIFE:

12 months (in original sealed container).

HEALTH & SAFETY:

Refer to MSDS