

TECHNICAL DATA SHEET

HPC 109 NU-FLAME FR OPAQUE WOOD FINISH

DESCRIPTION:

Nu-Flame Opaque Wood Finish is a water based flame retardant paint for new and previously painted timber

ADVANTAGES:

Nu-Flame Opaque Wood Finish gives a long lasting, all weather, microporous, protective, satin finish
Tested to BS 476 part 6 & 7 and satisfies Class '0' Requirements of current Building Regulations

USES:

For use on doors, skirting and other timber finishes.
Suitable for exterior use

COLOUR RANGE:

Burnt Walnut; Forest Green; Jacobean; Ebony; Rustic Oak and White.

PACK SIZE:

Single component product, supplied in 5 litre cans.

COVERAGE RATE:

Approximately 12 m² per litre depending on the nature and porosity of the surface being painted.
The final colour achieved will depend on the colour and porosity of the timber and the number of coats applied.
Do not apply when the temperature is below 10°C or when rain is imminent.

VOLUME SOLIDS

40% - LOW VOC CONTENT 0.30–7.99%

DRYING TIME:

Touch dry in 2–4 hours.
Recoat after 4 hours.
Allow first coat to dry before recoating.

PREPARATION:

Ensure surfaces to be treated are clean, free from contamination and dry.

APPLICATION:

By brush/roller.

EQUIPMENT CARE:

All equipment should be cleaned with water immediately after use

STORAGE:

Store away from direct sunlight and sources of heat.
Protect from frost.

SHELF LIFE:

12 months (in original sealed container).

HEALTH & SAFETY:

Refer to MSDS