

TECHNICAL DATA SHEET – HPC 111 NU-FLAME FR ACRYLIC EGGSHELL

DESCRIPTION:

Nu-Flame FR Acrylic Eggshell is a water based flame retardant paint for new and previously painted surfaces, timber and concrete where an eggshell finish is required.

ADVANTAGES:

When Nu-Flame Acrylic FR Eggshell is used it provides a washable finish for interior use.

Tested to BS 476 part 6 & 7 and satisfies Class '0' Requirements of current Building Regulations

USES:

For use on doors, skirting and other timber finishes as well as painted surfaces and concrete to complement the Nu-Flame wall finishes

COLOUR RANGE:

In any BS400 or RAL Shade.

PACK SIZE:

Single component product, supplied in 5 & 10 litre units.

COVERAGE RATE:

14 m² per litre

VOLUME SOLIDS

40%

DRYING TIME:

Touch: 2 Hours
Overcoat: 6 Hours

PREPARATION:

Ensure surfaces to be treated are clean, free from contamination and dry.

APPLICATION:

By brush/roller or Airless Spray

EQUIPMENT CARE:

All equipment should be cleaned with water immediately after use

STORAGE:

Store away from direct sunlight and sources of heat. Protect from frost.

SHELF LIFE:

12 months (in original sealed container).

HEALTH & SAFETY:

Refer to MSDS