

TECHNICAL DATA SHEET – HPC 13 NU-GUARD SB STABILISING PRIMER

DESCRIPTION:

Nu-Guard SB Stabilising Primer is a solvent based primer formulated to provide good brushing characteristics and good hold out for subsequent coats of paint.

ADVANTAGES:

Has excellent sealing properties and alkali resistance. Helps to provide a sound base for a durable paint system over chalky or friable surfaces.

USES:

For internal and external use as a primer for substrates likely to contain alkali salts such as unpainted dry plaster concrete rendered surfaces, for sealing powdery residues on many surfaces prior to using Nu-Guard SB Masonry Paint.

COLOUR RANGE:

Clear or White

PACK SIZE:

Single component product, supplied in 5 litres

COVERAGE RATE:

This is dependant upon the surface porosity. Average coverage rate is in the region of 8 – 10 m² per litre.

DRYING TIME:

Touch dry 2-4 hrs, Fully dry 24 hours

PREPARATION:

Ensure surfaces to be treated are clean, free from contamination and dry.

APPLICATION:

Brush, Roller or Airless Spray

EQUIPMENT CARE:

All equipment should be cleaned with Nu-Guard SB Brush Cleaner.

STORAGE:

Store away from direct sunlight and sources of heat. Protect from frost.

SHELF LIFE:

12 months (in original sealed container).

HEALTH & SAFETY:

Refer to MSDS