

TECHNICAL DATA SHEET – HPC 17 NU-GUARD NRG COLOUR TOPCOAT

DESCRIPTION:

Nu-Guard NRG Colour Topcoat is the final coat of a new generation, unique, coloured external coating system utilising the most advanced hybrid chemistry available to produce superior weather protection for masonry walls and bricks.

ADVANTAGES:

- Improve Energy Efficiency for Homes
- Super Hydrophobic Water Repellency
- Excellent Stain Resistance
- Resistant to Dirt and Pollution
- Self Cleaning Properties
- Resistant to Weathering
- UV Stability - Permanent
- Natural Clean Appearance
- Permeable to Water Vapour
- Protects Against Penetrating Damp

USES:

For use on all bare or previously painted external substrates.

COLOUR RANGE:

Any BS4800 or RAL Colour.

PACK SIZE:

Single component product supplied in 5, 10 or 15 Litre Tubs.

COVERAGE RATE:

This is dependant on texture and porosity of the substrate. On average the coverage rate is 10m²/ litre applied in 1 coat.

DRYING TIME:

Dry in 4-6 Hours @ 20°C



PREPARATION:

Apply when the Basecoat is sufficiently dry.

APPLICATION:

One coat by brush, roller or spray.

EQUIPMENT CARE:

All equipment should be cleaned with water immediately after use.

STORAGE:

Store away from direct sunlight and sources of heat. Protect from frost.

SHELF LIFE:

12 months (in original sealed container).

HEALTH & SAFETY:

Refer to MSDS