

TECHNICAL DATA SHEET – HPC 22 NU-GUARD MURAL BASECOAT

DESCRIPTION:

Nu-Guard Mural Basecoat is a waterbased coating with an excellent decorative appearance. Provides a solid background colour prior to the application of the Nu-Guard Mural Paint.

ADVANTAGES:

Extensive colour range giving the designer flexibility.

USES:

For use on previously painted substrates such as brickwork and concrete

COLOUR RANGE:

Available in any BS 4800 colour or RAL range.

Consult Hydron Technical Services Department.

PACK SIZE:

Single component product, supplied in 5 litre cans.

VOLUME SOLIDS:

40%

COVERAGE RATE:

This is dependant upon the surface porosity. Average coverage rate is in the region of 10 m² per litre.

DRYING TIME:

Touch Dry 1-2 hours

Overcoat 4 hours

Fully dry 12-24 hours



PREPARATION:

Ensure surfaces to be treated are clean, free from contamination and dry.

APPLICATION:

Brush, Roller or Airless Spray

EQUIPMENT CARE:

All equipment should be cleaned with water immediately after use.

STORAGE:

Store away from direct sunlight and sources of heat. Protect from frost.

SHELF LIFE:

12 months (in original sealed container).

HEALTH & SAFETY:

Refer to MSDS