

ISSUE: 04/01/2024

# **TECHNICAL DATA SHEET – HPC 55 NU-STEEL TP ETCH PRIMER**

## **DESCRIPTION:**

Nu-Steel TP Etch Primer is a two pack primer giving excellent adhesion to aluminium and other metal prior to subsequent paint systems.

## **ADVANTAGES:**

This is a high performance product giving protection up to 8 years.

### USES:

For use on properly prepared steel such as parapet/guard rails and architectural steelwork.

# **COLOUR RANGE:**

Yellow / Grey

# PACK SIZE:

Two component product, supplied in 10 litre units.

# **VOLUME SOLIDS:**

55%

# **COVERAGE RATE:**

15 m<sup>2</sup> / Litre

# **DRYING TIME:**

Touch: Overcoat: 1-2 Hours 4 Hours.

### **PREPARATION:**

Ensure surfaces to be treated are clean, free from contamination and dry. Previously coated surfaces should be abraded

# **APPLICATION:**

By brush/roller or spray.

# **EQUIPMENT CARE:**

All equipment should be cleaned with Nu-.Steel TP Thinners. Conventional thinners and brush cleaners are not effective.

### STORAGE:

Store away from direct sunlight and sources of heat. Protect from frost.

# SHELF LIFE:

12 months (in original sealed container).

### **HEALTH & SAFETY:**

Refer to MSDS

Unit 7 Phoenix Road Wednesfield Wolverhampton WV11 3PX, UK

TEL: +44(0) 1902 450 950

NGA. ISO 9001 Registered Quality Management

Data provided on this TDS is based on the best of our knowledge and experience, is given in good faith and should only be regarded as recommendations. No guarantee should be inferred and customers are advised to carry out their own tests under local conditions.