



TECHNICAL DATA SHEET – HPC 03 NU-GUARD PU FINISH

DESCRIPTION:

Nu-Guard PU Finish is a polyurethane based coating with additional anti graffiti additives added to give an excellent decorative appearance and outstanding resistance to solvents and chemicals, making it a first choice anti-graffiti coating for use on external surfaces.

ADVANTAGES:

Efficient graffiti removal with AG2 Graffiti Remover.

USES:

For use on a variety of substrates such as painted brickwork, render, concrete, metal and wood.

COLOUR RANGE:

Clear and any BS4800 or RAL Shade.

PACK SIZE:

Two component product, supplied in 5 litre units.

VOLUME SOLIDS:

50%

COVERAGE RATE:

10 m² / Litre

DRYING TIME:

Touch :.....2 hours.

Overcoat :4 hours.

PREPARATION:

Ensure surfaces to be treated are clean, free from contamination and dry.

APPLICATION:

By brush/roller or spray. Should not be applied at temperatures below 5°C or when the relative humidity exceeds 85%.

EQUIPMENT CARE:

All equipment should be cleaned with Nu-Guard PUThinner. Conventional thinners and brush cleaners are not effective.

STORAGE:

Store away from direct sunlight and sources of heat. Protect from frost.

SHELF LIFE:

12 months (in original sealed container).

HEALTH & SAFETY:

Refer to MSDS

