



TECHNICAL DATA SHEET – HPC 122 NU-BASE SP FLOOR PAINT

DESCRIPTION:

Nu-Base Single Pack Floor Paint is a fast drying floor paint based on a polyurethane modified alkyd resin. A non slip additive can be incorporated within the paint to provide a ready to use Anti Slip floor paint

ADVANTAGES:

Excellent decorative appearance with resistance to a wide range of mild chemicals and solvents. Anti slip benefits when incorporating the additive. Tested to BS7976 Parts 1-3 for slip resistance, Nu-Base SP Floor Paint achieves a 'Low Slip Potential' classification according to the H.S.E. in both dry and wet conditions.

USES: FerFA Class Type 1

Specially recommended for interior and exterior use on coated and uncoated concrete, stone, metal and wooden floor surfaces for medium traffic

COLOUR:

Available in 3 shades of Grey, Tile Red and Bottle Green.

COVERAGE RATE:

8 - 10m² / Litre

DRYING TIMES:

Touch dry	2 hours @ 20°C.
Overcoat	12 hours.

PACK SIZE:

Single component product, supplied in 5 litre cans.

PREPARATION:

All surfaces to be coated should be clean, dry and free from oil and grease etc. Ideally the substrate should be shot-blasted, mechanically abraded or acid etched with all loose, flaking materials and any laitance removed.

APPLICATION:

By brush or roller. 1st coat can be thinned with 10% Nu-Base SP Thinners. Allow to dry. This should then be overcoated with at least one full coat.

EQUIPMENT CARE:

All equipment should be cleaned with Nu-Base SP Thinners. Conventional thinners and brush cleaners are not effective.

STORAGE:

Recommended storage is in a cool, dry place with temperatures between 10-15°C, and in accordance with the Highly Flammable Liquids and Liquefied Petroleum Gases Regulations 1972.

SHELF LIFE:

12 months (in original sealed container).

HEALTH & SAFETY:

Refer to MSDS