



## TECHNICAL DATA SHEET – HPC 130 NU-BASE QD FLOOR PAINT

### DESCRIPTION:

Nu-Base QD Floor Paint is a fast drying floor paint based on tough acrylic resins. A non slip additive can be incorporated within the paint to provide a ready to use Anti Slip floor paint

### ADVANTAGES:

Low odour, quick drying and east to apply.  
Anti slip benefits when incorporating the additive.  
Tested to BS7976 Parts 1-3 for slip resistance, Nu-Base SP Floor Paint achieves a 'Low Slip Potential' classification according to the H.S.E. in both dry and wet conditions.

### USES: FeRFA Class Type 1

Specially recommended for interior and exterior use on coated and uncoated concrete, stone, metal and wooden floor surfaces for light traffic

### COLOUR:

Available in 2 shades of Grey, Tile Red and Bottle Green.

### COVERAGE RATE:

8 - 10m<sup>2</sup> / Litre

### DRYING TIMES:

Touch dry	1-2 hours @ 20°C.
Overcoat	4-6 hours.

### PACK SIZE:

Single component product, supplied in 10 litre tubs.

### PREPARATION:

All surfaces to be coated should be clean, dry and free from oil and grease etc. Ideally the substrate should be shot-blasted, mechanically abraded or acid etched with all loose, flaking materials and any laitance removed.

### APPLICATION:

By brush/roller or airless spray.1st coat thinned with 10% with water. Allow to dry. This should then be overcoated with at least one full coat.

### EQUIPMENT CARE:

All equipment should be cleaned with water

### STORAGE:

Recommended storage is in a cool, dry place with temperatures between 10-15°C, and in accordance with the Highly Flammable Liquids and Liquefied Petroleum Gases Regulations 1972.

### SHELF LIFE:

12 months (in original sealed container).

### HEALTH & SAFETY:

Refer to MSDS