



TECHNICAL DATA SHEET – HPC 132 NU-BASE PS FLOOR FINISH

DESCRIPTION:

Nu-Base PS Floor Finish is a Polysiloxane-based coating with an excellent decorative appearance and outstanding resistance to solvents and chemicals, making it a first choice pigmented floor coating for use on external surfaces.

ADVANTAGES:

UV Stable, Chemical Resistant and fast drying times.

USES:

For use on a variety of floor substrates such as concrete, wood and GRP

COLOUR:

Any BS4800 or RAL Shade

COVERAGE RATE:

16 m² / Litre

DRYING TIMES

Touch dry	2 hours @ 20°C.
Overcoat	4 hours.
Full Cure	7 days.

POT LIFE:

1 Hour @ 20°C

VOLUME SOLIDS:

90 %

PACK SIZE

Two component product, supplied in 5 litre units.

PREPARATION:

All surfaces to be coated should be clean, dry and free from oil and grease etc. Ideally the substrate should be shot-blasted, mechanically abraded or acid etched with all loose, flaking materials and any laitance removed.

APPLICATION:

By brush/roller or airless spray

EQUIPMENT CARE:

All equipment should be cleaned with Nu-Guard HS Thinners. Conventional thinners and brush cleaners are not effective.

STORAGE:

Recommended storage is in a cool, dry place with temperatures between 10-15°C, and in accordance with the Highly Flammable Liquids and Liquefied Petroleum Gases Regulations 1972.

SHELF LIFE:

12 months (in original sealed container).

HEALTH & SAFETY:

Refer to MSDS