



TECHNICAL DATA SHEET – HPC 136 NU-BASE ACRYLIC BLOCK SEAL

DESCRIPTION:

Nu-Base Acrylic Block Seal is a specifically formulated quick drying acrylic sealant designed to protect concrete and block paving against the ingress of water, dirt, oil, grease and a wide range of chemicals.

ADVANTAGES:

Single pack ready for immediate use. Will consolidate jointing sand and help stop the growth of moss and weeds, and will provide a cost effective hard wearing, quick drying, durable and chemical resistant finish.

USES:

Nu-Base Acrylic Block Seal is for use on concrete and block paving.

COLOUR:

Clear.

COVERAGE RATE:

This is dependent upon the surface porosity. Average coverage rate is in the region of 3-5 m² per litre.

DRYING TIMES

Touch dry.....40 Minutes@ 20°C.

Overcoat..... ..1 hour.

PACK SIZE

Single component product, supplied in 25 litre cans.

PREPARATION:

Ensure surfaces to be treated are clean, free from contamination and dry. All loose materials should be swept away and laitance removed by etching with Nu-Base Acid Etch. The surface should then be washed off to provide a clean neutral surface and allowed to dry overnight.

APPLICATION:

By brush/roller or low pressure spray

EQUIPMENT CARE:

All equipment should be cleaned with Xylene. Conventional thinners and brush cleaners are not effective.

STORAGE:

Store away from direct sunlight and sources of heat. Protect from frost.

SHELF LIFE:

12 months (in original sealed container).

HEALTH & SAFETY:

Refer to MSDS