



TECHNICAL DATA SHEET – HPC 139 NU-BASE EPOXY FLOOR PRIMER

DESCRIPTION:

Nu-Base Epoxy Floor Primer is a two pack epoxied resin bonding agent.

ADVANTAGES:

Nu-Base Epoxy Floor Primer has good wetting our properties, will act as a damp-proof membrane provided no water pressure exists.
Will cure under damp conditions.

USES:

For use as a primer in conjunction with Nu-Base Contract Screed and Epoxy Finishes

COLOUR:

Straw

COVERAGE RATE:

3-5 m² / KG

DRYING TIMES

Touch dry	6 hours @ 20°C.
Overcoat	2 - 4 hours.
Full Cure	7 days.

POT LIFE:

30 minutes @ 20°C

VOLUME SOLIDS:

100 %

PACK SIZE

Two component product, supplied in 1 Kg., 2.5 Kg. and 5 Kg units.

PREPARATION:

New floors must be clean, dry and fully cured. Shot blast to provide a surface profile and ensure penetration. Old floors remove all dirt, oil, grease and other contamination by shot-blasting, scarification or mechanical planning

APPLICATION:

By brush/roller or airless spray

EQUIPMENT CARE:

All equipment should be cleaned with Nu-Base Epoxy Thinners. Conventional thinners and brush cleaners are not effective.

STORAGE:

Recommended storage is in a cool, dry place with temperatures between 10-15°C, and in accordance with the Highly Flammable Liquids and Liquefied Petroleum Gases Regulations 1972.

SHELF LIFE:

12 months (in original sealed container).

HEALTH & SAFETY:

Refer to MSDS