



TECHNICAL DATA SHEET – HPC 45 NU-CRYL® AG RENDERCOAT

DESCRIPTION:

Nu-Cryl AG Render Coat is a unique, clear, hydrophobic impregnation coating system suitable for application to self coloured render.

ADVANTAGES:

Nu-Cryl AG Render Coat will not noticeably change the appearance of the substrate. Due to its excellent stain resistant and water repellent qualities, dirt, pollution, and even graffiti can be removed from the treated surface. The system gives long life graffiti and environmental protection. It has outstanding resistance to weathering and ultra-violet degradation, and no reapplication is required after graffiti removal. **Satisfies Class'0' requirements of current Building Regulation.**

USES:

For use on self coloured render, stucco and plaster surfaces.

COLOUR:

Clear / Invisible

COVERAGE RATE:

This is dependent on texture and porosity of the substrate. The figures quoted below are given only as guidance.

| | |
|----------------------|--------------------------|
| Self coloured render | 3m ² /Ltr |
| Stucco | 4 – 5m ² /Ltr |
| Plaster | 6m ² /Ltr |

PACK SIZE

Supplied in 5, 25, 200, 1000 litres

PREPARATION:

Ensure surfaces to be treated are clean, free from contamination and dry. Treat all areas affected by organic growth with Hydron SS1 Sterilising Solution.

APPLICATION:

Shake the container well before use. Application by low pressure spray or by brush/roller to saturation point either in one application or in two applications. Apply the second application in the same manner after allowing to dry for 1-2 hours. On vertical surfaces apply, apply from the bottom up.

EQUIPMENT CARE:

All equipment should be cleaned with water immediately after use.

STORAGE:

Store away from direct sunlight and sources of heat. Protect from frost.

SHELF LIFE:

12 months (in original sealed container).

HEALTH & SAFETY:

Refer to MSDS