



TECHNICAL DATA SHEET – NU-STEEL CLADDING PAINT

DESCRIPTION:

Nu-Steel Cladding Paint is a single pack, modified acrylic paint specifically developed for application to Plastisol and polyester coated steel and aluminium cladding.

ADVANTAGES:

Will provide excellent resistance to UV attack

USES:

For use on properly prepared cladding and prefabricated buildings, architectural steelwork, and industrial environments.

PREPARATION:

Ensure surfaces to be treated are clean, free from contamination and dry. Degrease plastisol with MC1 Multiclean and rinse down with clean water. Allow to dry.

APPLICATION:

By brush/roller or Airless Spray

EQUIPMENT CARE:

All equipment should be cleaned with T5 Thinners.

STORAGE:

Store away from direct sunlight and sources of heat. Protect from frost.

SHELF LIFE:

12 months (in original sealed container).

HEALTH & SAFETY:

Refer to MSDS

	HPC 61 Cladding Primer	HPC 62 Cladding Finish
COLOUR	White/Grey	Any RAL / BS4800 Colour
PACK SIZE	S.P 5 Litres	S.P 5 Litres
COVERAGE	8 m ² /litre	6 m ² /litre
DRYING TIME	4 Hours 8 Hours	3 Hours 24 Hours