

ISSUE: 04/01/2025

TECHNICAL DATA SHEET – HPC 89 NU-FLAME NEW PLASTER SEALER

	DESCRIPTION:	DRYING TIME:	
	Nu-Flame New Plaster Sealer is a smooth, non-toxic, water-soluble sealer for plaster, used as part of the Nu-Flame Fire Upgrade Coating System.	Touch: Overcoating:	2 hours 4 hours
	ADVANTAGES: Single pack ready for immediate use.	PREPARATION: Ensure surfaces to be treated are clean, free from contamination and dry.	
	USES:	APPLICATION:	
	Internal decorative paint system.	By brush/roller or spray.	
	COLOUR RANGE:	EQUIPMENT CARE:	
	White and pastel shades.	Clean equipment with water immediately after use.	
	PACK SIZE:	STORAGE:	
	Single component product, supplied in 10 litres	Store away from direct sunlight and sources of heat. Protect from frost.	
COVERAGE RATE: 10 m ² per litre.		SHELF LIFE: 12 months (in original sealed container).	
		HEALTH & SAFETY: Refer to MSDS	



Data provided on this TDS is based on the best of our knowledge and experience, is given in good faith and should only be regarded as recommendations. No guarantee should be inferred and customers are advised to carry out their own tests under local conditions.

N55Plus