

## TECHNICAL DATA SHEET – HPC 99 NU-FLAME FR COLOURCOAT

### DESCRIPTION:

Nu-Flame FR Colour Coat is a flame retardant paint finish.

Also used as a basecoat for use prior to multi-coloured finishes.

### ADVANTAGES:

Being a water soluble product this is safe for internal applications. **Tested to BS 476 part 6 & 7 and satisfies Class '0' Requirements of current Building Regulations.**

### USES:

For use on walls and ceilings.  
Intermediate coat of the Nu-Flame Multi-coloured System.

### COLOUR RANGE:

In any BS400 or RAL Shade.

### PACK SIZE:

Single component product, supplied in 5 & 10 litre units.

### COVERAGE RATE:

14 m<sup>2</sup> per litre

### VOLUME SOLIDS

40%

### DRYING TIME:

Touch: 2 Hours  
Overcoat: 4 Hours

### PREPARATION:

Ensure surfaces to be treated are clean, free from contamination and dry.

### APPLICATION:

By brush/roller or Airless Spray

### EQUIPMENT CARE:

All equipment should be cleaned with water immediately after use

### STORAGE:

Store away from direct sunlight and sources of heat.  
Protect from frost.

### SHELF LIFE:

12 months (in original sealed container).

### HEALTH & SAFETY:

Refer to MSDS